



## TB & TPB TRIPLE PURPOSE FOG NOZZLES



The TB & TPB range of triple purpose nozzles offers a variety of capacities to meet individual specifications. These nozzles are robust, compact and dependable with straight jet, spray & water curtain settings.

**OPERATION:** By rotating the head from the shut-off position, the operator can change from a straight jet to a fine water curtain. This fog pattern can be varied from 30° to 120°.

**CONSTRUCTION:** These fog nozzles are available in brass (TB), high aluminium alloy (TA) or high density plastic outer body combined with brass inner body and hose connector (TPB). All models have large impact protection rings to reduce damage.

### SPECIFICATIONS:

Nozzle Size	AWFS Part No's	Material	BSP Female Connection	Height of Unit	Pressure at Nozzle kPa	Capacity litres/minute			Length of Throw			Height of Throw metres
						Str't Jet	30° Fog	Water Curtain	Str't Jet	30° Fog	Water Curtain	
TB25	NTB2538	Brass	38mm	150mm	345	170	185	340	19.8	12.2	10.6	12.2
TA25	NTA2538	Alloy			690	212	227	400	25.9	19.8	13.7	16.7
					1035	283	329	453	33.5	22.9	16.8	21.3
TPB15	NTPB1525 / NTPB1538	Brass/PVC	25mm &	108mm	345	75	83	166	13.7	0.6	6.1	12.2
TB15	NTB1525 / NTB1538	Brass	38mm		690	91	98	196	15.2	11.6	8.5	13.7
TA15	NTA1525	Alloy	25mm		1035	106	113	234	18.3	14	9.7	15.2
TB10	NTB1019 / NTB1025	Brass	19mm &	85mm	345	30	34	57	8.5	8.5	6.1	10.0
TPB10	NTPB1019 / NTPB1025	Brass/PVC	25mm		690	41	45	72	9.1	10.4	9.1	11.6

